



NSB 110 FT

KEY FEATURES

- Specifically designed for indoor/outdoor telecom applications.
- Compliant with 19", 23" and ETSI racking dimensions.
- 10 year float life at 25°C (77°F) — 15 year float life at 20°C (68°F).
- Flame retardant (UL 94 VO) PC-ABS plastic case and cover.
- 3 step terminal seal design to ensure leak-free operation. Female M8 brass terminals—numerous adapter kits available.
- Remote gas emission system included for enclosed cabinet applications.
- Integral handles ensure ease of handling.
- Approved as non-hazardous cargo for ground, sea and air transportation.

ELECTRICAL CHARACTERISTICS

Refer to the NSB detailed performance tables for additional current, capacity and power information.

	<i>Int'l Standards @ 20°C</i>	<i>NA Standards @ 77°F</i>
8 hour capacity to 1.75 VPC	108.9 amp-hours	111.4 amp-hours
10 hour capacity to 1.80 VPC	110 amp-hours	112.4 amp-hours
Float voltage	2.29 +/- .02 volts per cell	2.27 +/- .02 volts per cell
Cyclic Recharge	2.45 VPC — no current limit	
Shelf life	2 years	
Impedance (1KHz)	2.2 mΩ	
Short Circuit Current	4,000 Amps	
Voltage	12 Volts	

MECHANICAL CHARACTERISTICS

	<i>SI Units</i>	<i>English Units</i>
Height	227 mm	8.94 inches
Width	125 mm	4.92 inches
Length	560 mm	22.05 inches
Weight	41.4 kilograms	91.3 pounds
Terminal Torque	8.0 Newton-meters	71 inch-pounds

ALL NORTHSTAR
PRODUCTS ARE
COMPLIANT WITH:

- ★ Telcordia SR4228
- ★ Bellcore GR-63-Core, Issue 1
- ★ DOT 49CFR173.159(d) (i) and (ii)
- ★ UL Approval
- ★ ISO 9000/14000
- ★ BS6290(iv)