

TELECOM



ALL NORTHSTAR PRODUCTS ARE COMPLIANT WITH:

- ✦ Telcordia SR4228
- ✦ Bellcore GR-63-Core, Issue 1
- ✦ DOT 49CFR173.159(d) (i) and (ii)
- ✦ UL Approval
- ✦ ISO 9000/14000
- ✦ British and German telecom standards

NSB 40 FT

KEY FEATURES

- Specifically designed for mission-critical applications. Excels at high-rate discharge and recharge, extreme temperature range, deep or shallow cyclic applications.
- High cyclic life capability +500 C/3 @ 80% DOD.
- 10 year float life at 25°C (77°F) — 15 year float life at 20°C (68°F).
- Flame retardant (UL 94 VO) PC-ABS plastic case and cover.
- 3 step terminal seal design to ensure leak-free operation. Female M6 brass terminals provide maximum high rate performance and no annual retightening.
- Approved as non-hazardous cargo for ground, sea and air transportation.

ELECTRICAL CHARACTERISTICS

Refer to the NSB detailed performance tables for additional current, capacity and power information.

	Int'l Standards @ 20°C □	NA Standards @ 77°F
8 hour capacity to 1.75 VPC □	38 amp-hours □	39 amp-hours □
10 hour capacity to 1.80 VPC □	39 amp-hours □	40 amp-hours
Float voltage □	2.29 +/- .03 volts per cell □	2.27 +/- .03 volts per cell
Cyclic Recharge □	2.45 VPC — no current limit	
Shelf life □	2 years	
Impedance (1KHz) □	6.5 m□ □	
Short Circuit Current □	1,400 Amps □	
Voltage □	12 Volts □	

MECHANICAL CHARACTERISTICS

	SI Units □	English Units
Height □	207 mm □	8.14 inches □
Width □	94 mm □	3.72 inches
Length □	250 mm □	9.84 inches
Weight □	12.7 kilograms □	27.9 pounds
Terminal Torque □	8.0 Newton-meters □	71 inch-pounds