

## UNINTERRUPTIBLE POWER SYSTEMS



# Remote-D

## Intelligent Power Distribution Unit

- Protection of Electronic Equipment from Random Surges and High Amplitude Spikes
- Comprehensive Power Management via RS232 and Ethernet with Browser or SNMP
- Remote Management Individual Output Power Receptacles
- Programmable Turn On/Off Based on Specific Events
- Event Notification through SNMP Trap and Email Alerts
- Detailed Data-Logging For Statistic Analysis and Diagnostics
- Double-Layer Security for Administrators and Users
- Optional Connectivity of Versatile Sensors via Environmental Monitoring Device

# Remote-D Intelligent Power Distribution Unit

MODEL		Remote-D-120V	Remote-D-230V
<b>INPUT</b>	Voltage	120 Vac	230 Vac
	Voltage Range	100 – 125 V	200 – 250 V
	Load Capacity	15 A	15 A
	Frequency	50/60 Hz Auto Sensing	
	Input Line Cord	5 - 15P	IEC C14
	Line Cord Length	6 ft	
<b>OUTPUT</b>	Voltage	120 Vac	230 Vac
	Frequency	50/60 Hz Auto Sensing	
	Rated Current	15 A	10 A
	Output	Eight NEMA 5-15R	Eight IEC C13
<b>COMMUNICATION</b>	Network Protocol	SNMP over UDP/IP, HTTP over TCP/IP	
	Network Security	SNMPv3, SSL, SSH	
	Support MIB	Remote-D MIB	
	Security	Secure Password Protection	
<b>PHYSICAL</b>	Output Power Status Indications	Displays Output Current, Power Status, Remote Control Status	
	Input Power Consumption Indication	Displays Percentage of Input Power Consumed	
	Status Indication	Displays Input Current, Voltage, Frequency & Error Code	
	Remote Control Buttons	Manually Control Output Power & Remote Control	
	Reset Button	Hard Reset of Remote-D	
	Dip Switches	Upgrade & Diagnosis Purpose	
	Console Port	Configuration Purpose & EMD Connectivity	
	Network Port	10/100 Base T RJ-45 Network Connectivity	
	Input Power Outlet	Connects to Power Output	
	System Breaker	Prevents Excessive Current Flow	
	Two Set Digital Contacts	Events Controlled Contacts	
	Dimensions W x D x H (mm)	436 x 270 x 44	
	Ship Dimensions W x D x H (mm)	541 x 366 x 136	
	Dimensions W x D x H (inch)	17.2 x 10.6 x 1.73	
	Ship Dimensions W x D x H (inch)	21.3 x 14.4 x 5.4	
	Weight lb (kg)	8.4 (3.8)	
Ship Weight lb (kg)	12 (5.5)		
<b>OPTION</b>	Environmental Monitoring Device	Part #: RMTI-EMD-HT	
<b>ENVIRONMENT</b>	Operating Ambient Temperature	0 – 40°C	
	Recommended Temperature	15 – 25°C	
	Storage Temperature	-15 – 50°C	
	Humidity	10 – 80% Non-condensed	
<b>CONFORMANCE</b>	Regulatory Approvals	FCC Class A, UL, CUL, CE	
<b>WARRANTY</b>		Two Year	



Remote-D-120V (Rear)



Remote-D-230V (Rear)

**UPS    ADJUSTABLE SPEED DRIVES    MOTORS    CONTROLS    INSTRUMENTATION    PLC**

## TOSHIBA

Available Through:

**TOSHIBA INTERNATIONAL CORPORATION**

**INDUSTRIAL DIVISION**

13131 West Little York Road, Houston, Texas 77041

Tel (713)466-0277 Fax (713)466-8773

US (800)231-1412 Canada (800)872-2192 Mexico 01(800)527-1204

www.toshiba.com/ind

Copyright 3/2006

