

# SmartOnline Expandable Rack / Tower UPS System

Online, double-conversion protection for mission critical applications



## Model #: SU3000RTXL3U

- ▶ 3000VA online 3U expandable rack / tower UPS
- ▶ Enhanced serial communications port and SNMP/Web card slot
- ▶ Maintains 120V +/-2% output during overvoltages to 138 and brownouts as low as 65V
- ▶ 2 load banks, 9 outlets (5-15, 5-20, L5-30)
- ▶ Fault tolerant auto-bypass
- ▶ \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

## DESCRIPTION

Tripp Lite's SmartOnLine SU3000RTXL3U on-line, double conversion UPS protects critical server, networking or telecommunications equipment from blackouts, voltage fluctuations and surges. Multi-use form factor occupies only 3 rack spaces (3U) in standard 19 inch rackmount configuration and includes tower stands to support upright placement. Large capacity 3kVA / 2400 watt UPS continuously converts incoming AC to DC, then back to perfect sine wave AC output at 120V AC (+/-2%). Removes harmonic distortion, fast electrical impulses, frequency fluctuations and other hard-to-solve power problems not addressed by other UPS types. True sine wave output and zero transfer time offers guaranteed compatibility with all equipment types. Includes 9 outlets arranged in two individually switchable load banks. These outlet banks can be independently controlled via software interface to selectively reboot remote equipment, or shed less critical loads to extend battery runtime for more critical equipment. Battery support can be extended indefinitely through the addition of external 2U rackmount battery packs (part# BP72V12-2U). Includes slot for internal SNMP/web card, plus DB9 enhanced serial monitoring port for unattended shutdown, remote control and monitoring of UPS system and power data. Compatible with Tripp Lite's Watchdog system service software.

## KEY BUYING POINTS

- True on-line, double conversion UPS provides pure, sine wave AC output at all times
- Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time
- Removes harmonic distortion, electrical impulses, frequency variations and other hard to solve power problems
- Accepts input voltages between 80 and 138 (65 to 138 at loads under 70%), regulating output to 120V +/-2%
- 3000VA / 2400 watt power capacity with 9 total outlets (4 NEMA5-15R, 4 NEMA5-20R & 1 NEMAL5-30R)
- Standard internal battery set provides 17 minutes runtime at half load
- Expandable runtime with multiple external battery packs (part# BP72V12-2U)
- Innovative design makes unit adaptable for rackmount, tower, or stacking applications
- Uses only 3 rack spaces (3U) in standard 19 inch rack
- DB9 serial port for network interface; SNMP compatible
- Slot for optional SNMP/web card (part# SNMPWEBCARD)
- PowerAlert unattended shutdown software and 6 ft. network cable included
- Compatible with Tripp Lite's Watchdog system service software
- Fault tolerant auto-bypass maintains continuous utility output to connected equipment with no disruption in output AC, even in cases where the UPS is overloaded or experiences major component failure and requires service
- Diagnostic LEDs
- Battery replacement door
- Mounting hardware included for 4 post rack enclosures, optional 2POSTRMKIT accessory enables installation in 2 post telecom racks
- \$250,000 Ultimate Lifetime connected equipment insurance
- 2 year manufacturers product warranty

## TYPICAL APPLICATIONS

- Ideal for protection of critical 120V equipment in server rooms, internetworking closets and telecommunications systems in rackmount or tower applications. Common applications include corporate or departmental servers, workstations, hubs, routers, bridges, CAD/CAM workstations, concentrators, IP telephony and traditional PBX switching systems.

## OPTIONS & ACCESSORIES

- External battery pack: [BP72V122U](#)
- SNMP accessories: [SNMPCARD](#), [SNMPWEBCARD](#), [ENVIROSENSE](#)
- Dataline protectors: [DNET1](#), [DTEL2](#), [DCATV](#)
- Circuit Tester: [CT120](#)
- Rack enclosures: [SRNET45UB](#), [SR45U](#), [SR45UB](#), [SRX24UB](#)
- Power distribution: [PDU2430](#), [PDU1220](#), [PS7224-20](#)
- Two Post Rackmount Kit: [2POSTRMKIT](#)
- Extended warranties: 3 Year [WEXT3-2200-3000](#), 5 Year [WEXT5-2200-3000](#)

## PACKAGE INCLUDES

- SU3000RTXL3U Rack-Tower UPS System
- PowerAlert Software and cabling
- Mounting hardware for 4 post rackmount installation / tower stands
- Warranty information
- Instruction manual

## COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
<b>System overview:</b>	Online, double conversion 3U rack / tower UPS system continuously maintains near-perfect output power for critical internetworking and telecommunications equipment. Completely regenerates input power into perfectly regulated sine wave output free of harmonic distortion, fast electrical impulses and frequency fluctuations. Maintains output within 2% of 120V during brownouts as low as 65V and overvoltages to 138V. Supports enhanced monitoring of UPS and line power conditions via DB9 serial port, included PowerAlert monitoring software and complete cabling. Includes slot for SNMPWEBCARD and 2 individually controllable output load banks. Runtime is expandable with BP72V122U battery packs.
<b>Voltage compatibility:</b>	120V
<b>Frequency compatibility:</b>	50/60 Hz compatible
OUTPUT	
<b>Output volt amp capacity (VA):</b>	3000
<b>Output watt capacity (watts):</b>	2400
<b>Output nominal voltage:</b>	120V AC
<b>Output voltage regulation:</b>	Maintains full-time sine wave output within 2% of 120V, less than 5% total harmonic distortion
<b>Output frequency regulation:</b>	Regulates line frequency to 50/60Hz +/- 0.05Hz
<b>Outlet quantity / type:</b>	9 outlets (4 NEMA5-15R, 4 NEMA5-20R, 1 NEMA L5-30)
<b>Customized load management receptacles:</b>	2 individually controllable load banks support automated load shedding and remote reboot on demand of locked network devices. Configurable via PowerAlert software to automatically switch off optional loads, like monitors, to increase available runtime for servers and other critical devices. (Bank A consists of 4 outlets / Bank B consists of 4 outlets)
<b>Overload protection:</b>	Via 40A input breaker
INPUT	
<b>Maximum input amps:</b>	22A / 2844 watts max.
<b>Input connection type:</b>	NEMA L5-30P
<b>Input cord length:</b>	10 ft. 10 gauge

<b>Recommended electrical service:</b>	30A 120V
<b>BATTERY</b>	
<b>Full load runtime:</b>	Internal batteries — 6 min. 1 BP72V122U (3000VA) — 17 min.
<b>Half load runtime:</b>	Internal batteries — 17 min. 1 BP72V122U (1500VA) — 37 min.
<b>Expandable battery runtime:</b>	Supports extended runtime with optional external battery pack BP72V122U (multi-pack compatible)
<b>DC system voltage:</b>	72 V DC
<b>Typical battery lifespan:</b>	3-6 years, depending on usage
<b>Battery recharge rate:</b>	2-4 hours to 90%
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description:</b>	On-line, double-conversion power conditioning maintains output within 2% of 120 volts at all times
<b>Ovvervoltage correction:</b>	Maintains output of 120V +/-2% during overvoltages to 138V AC
<b>Brownout correction:</b>	Maintains output of 120V +/-2% during undervoltages to 80V AC
<b>Severe brownout correction:</b>	At load levels less than 70%, UPS maintains output of 120V +/-2% during undervoltages to 65V AC
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Front panel LEDs:</b>	6 LED STATUS DISPLAY: line power (green), online (green), bypass (yellow), on battery (green), overload (red), battery low (yellow) 4 LED LOAD / BATTERY LEVEL DISPLAY (100%, 75%, 50%, 25%)
<b>Alarms:</b>	Multi-function audible alarm offers notification of UPS start, backup operation, low battery warning, overload, UPS fault and remote shutdown
<b>Switches:</b>	Includes main power off/on switch, plus 1 switch to select battery charge / load level display
<b>SURGE / NOISE SUPPRESSION</b>	
<b>AC surge suppression:</b>	2440 joules
<b>AC suppression response time:</b>	Instantaneous
<b>EMI / RFI AC noise suppression:</b>	Yes
<b>PHYSICAL</b>	
<b>Shipping weight (lbs):</b>	90.3
<b>Shipping weight (kg):</b>	41.0
<b>Unit weight (lbs):</b>	74.9
<b>Unit weight (kg):</b>	34.0
<b>Unit Dimensions (HWD/in):</b>	5.25 x 17.5 x 19.8
<b>Unit Dimensions (HWD/cm):</b>	13.3 x 44.5 x 50.3
<b>Material of construction:</b>	Steel
<b>Form factors supported:</b>	Supports 3U rackmount installation in 4 post rack enclosures. 2 post rackmount installation supported with optional 2POSTRMKIT. Upright tower installation supported with included tower stands
<b>Cooling method:</b>	Built-in cooling fan
<b>Battery Access:</b>	User replaceable, hot swap battery replacement supported via front access panel
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature:</b>	+32 to +104 degrees Fahrenheit 0 to +40 degrees Celsius
<b>Storage Temperature:</b>	+5 to +122 degrees Fahrenheit

	-15 to +50 degrees Celsius
Relative Humidity:	0 to 95%, non-condensing
<b>COMMUNICATIONS</b>	
Network monitoring port:	One built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure basic monitoring capability
Software and cabling included:	Yes, includes PowerAlert software CD-ROM and complete cabling
SNMP compatibility:	Yes, includes slot for optional SNMPWEBCARD accessory (#SNMPWEBCARD)
WatchDog compatibility:	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
<b>LINE / BATTERY TRANSFER</b>	
Transfer time from line power to battery mode:	Zero, online UPS continuously converts incoming AC to DC, then back to AC. When commercial power is interrupted, UPS maintains continuous output from battery reserves with absolutely no disruption in output AC power.
Low voltage transfer to battery power:	Maintains continuous operation during undervoltages as low as 80V (65V at load levels under 70%). Below this switchover point, output is supported from battery derived AC power.
High voltage transfer to battery power:	Maintains continuous operation without using battery power during overvoltages to 138V. Above this point, output is supported from battery derived AC power.
<b>CERTIFICATIONS</b>	
Certifications:	UL1778 (USA), cUL (Canada), FCC Class A (emissions), NOM (Mexico)
<b>WARRANTY</b>	
Optional coverage:	3-5 year warranties, plus next day and on-site warranty coverage available for select opportunities. Contact Tripp Lite for additional information.
Product warranty:	2 year product warranty
Connected equipment insurance (USA and Canada Only):	\$250,000 connected equipment insurance (USA and Canada only)
<b>SPECIAL FEATURES</b>	
EPO port:	Supports "Emergency Power Off" via special-order cabling, contact Tripp Lite for more information
Cold Start:	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance:	Attractive black steel rackmount housing
<b>BATTERY PACK ACCESSORY (optional)</b>	
Battery Pack Accessory (optional):	BP72V122U (optional)

*The policy of Tripp Lite is one of continuous improvement.  
Specifications are subject to change without notice.  
Therefore, your product may vary slightly from what is currently listed.*



**Tripp Lite World Headquarters**  
1111 W. 35th Street  
Chicago, IL 60609 USA

**Customer Support**  
(773) 869-1234

© 2004 Tripp Lite. All Rights Reserved.