



Liebert Series 610 1000 kVA UPS

Power Availability

RELIABLE POWER FOR LARGE DATA CENTERS AND FACTORIES

When your facility can't afford any unplanned outages, you need the Uninterruptible Power Supply system with the best reliability record in the business. The Series 610 is based on a conservative design philosophy that has produced field-documented critical bus MTBF in excess of two million hours, based on actual field experience.

The Liebert Series 610 UPS modules are 93% efficient at full load—performance that rivals or exceeds many competitive products.

Standard features include:

- 12-pulse 3-phase rectifier/charger
- Input and Output isolation transformers
- Electrically operated output circuit breaker and wrap-around bypass circuit breaker on Single-Module Systems (SMS)
- Static bypass switch with isolators on SMS
- Bypass pulse-parallel on SMS and Automatic retransfer on SMS
- Enhanced output critical bus and internal fault management
- High overload capability
- Two-step input current limit and two-step battery charger current limit
- Automatic equalize charger and timer
- Application Specific Integrated Circuits (ASICs)
- Microprocessor-based monitoring with easy-to-read back-lit LCD display
- User prompted menu program
- Metering
- Visual & Audible alarms
- Remote E.P.O. provisions
- Redundant cooling fans
- Front access for maintenance and service

The Liebert Series 610 Gives You Power Protection In Many Configurations:

- Single-Module Systems
- Multi-Module Systems
- Parallel Redundant Systems
- Isolated Redundant Systems
- Load Bus Synchronized Systems
- Liebert Power-Tie™ Systems

These models are the flagships of the Liebert Series 610 product line. They provide clean, reliable power for hundreds of data centers, telecommunication centers, process control facilities, and other locations housing sensitive electronic equipment around the world.



Liebert Series 610 1000 kVA UPS

Power Availability

General Specifications

Ups Rating			Ac Input / Output Voltage	Efficiency At 100% Load	Nominal Battery Requirements	Maximum Heat Dissipation At Full Load	Dimensions WxDxH ²	Approx. Weight (LB.) ²	
kVA	kW	Power Factor	(VAC)	(%)	(CELLS)	(BTU/Hr)	(INCHES)	SMS	MMU
1000	900	0.9	480 or 600	93	240	231,200	177x44x82	16,700	16,555

¹Efficiency measured at rated power factor

²Dimensions and weights do not include System Control Cabinet furnished with Multi-Module Systems

Input

Voltage: 480 or 600 VAC, 3-phase, 3-wire plus ground.

Voltage Range: +10, -15% (no battery discharge down to -20%)

Power Factor: 0.95 lagging at full load with input filter (0.85 without).

Frequency Range: 60 Hz, $\pm 5\%$.

Current Distortion: 4% maximum reflected THD at full load with optional input filter (9% without).

Subcycle Magnetizing Inrush: 5-8 times normal full load current.

Walk-In: Configurable walk-in of 20% to 100% in 15 seconds.

Output and Bypass

Voltage: 480 or 600 VAC, 3-phase, 3-wire or 4-wire plus ground.

Voltage Adjustment: $\pm 5\%$.

Voltage Regulation: $\pm 0.5\%$ for balanced load; $\pm 2\%$ for 50% unbalanced load.

Dynamic Regulation: $\pm 8\%$ deviation for 100% load step. $\pm 5\%$ deviation for 50% load step. $\pm 1\%$ for loss or return of AC input. Manual return of load to UPS: $\pm 4\%$.

Transient Response Time: Recover to $\pm 1\%$ of steady state within 50 milliseconds.

Voltage Distortion: For linear loads, 5% THD, maximum total. 3% RMS maximum for any single harmonic. Less than 5% THD for 100% nonlinear loads without kVA/kW derating.

Phasing Balance: $120^\circ \pm 1^\circ$ for balanced load. $120^\circ \pm 3^\circ$ for 50% unbalanced load.

Frequency Regulation: $\pm 0.1\%$.

Load Power Factor Range: Unity to rated lagging power factor without derating.

Overload: 125% of full load for ten minutes. 150% for 30 seconds. 104% continuous.

Fault-Clearing Current: Up to 1000% for 16 milliseconds up to 500% for 40 milliseconds.

Environmental

Operating Temperature: 0° to 40°C without derating.

Non-Operating Temperature: -20°C to 70°C .

Humidity: 0-95% relative humidity without condensation.

Operating Altitude: Up to 4,000 feet (1200 meters) without derating.

Non-Operating Altitude: Up to 50,000 feet (15,000 meters).

Audible Noise: 75 dBA typical, measured 5 feet from the unit.

Physical

ETL Listed to UL 1778 UPS standards, and CSA certified. Meets requirements for safe high performance UPS operation.

Standard Features

- Easy-to-read backlit LCD monitor/control display panel
- Self-diagnostics
- Output isolation transformer
- 2-stage battery charge current limit
- 2-stage input AC current limit
- Internal wrap-around bypass
- Automatic and programmable retransfer
- Automatic line-drop compensation
- Battery overdischarge protection
- Battery-time-remaining display and battery statistics
- Automatic equalize charge timer
- Emergency Power Off (EPO)
- Front access only for service and maintenance

Options and Accessories

- Input filter/power factor correction
- 12-pulse rectifier input (for 500-750 kVA)
- Load Bus Sync™ (for dual load bus systems)
- Power-Tie®Dual-Bus System
- Bypass isolation transformer
- Maintenance bypass cabinet matching or panelboard
- Power distribution unit (single or dual input)
- Standard and custom switchgear packages
- Valve-regulated lead-acid battery packs
- Flooded rack-mounted battery systems
- SNMP capabilities
- Remote monitor panel
- Communications interfaces
- Alarm status contacts
- Customer alarm inputs

LIEBERT CORPORATION

1050 DEARBORN DRIVE
P.O. BOX 29186
COLUMBUS, OHIO 43229
800.877.9222 PHONE (U.S. & CANADA ONLY)
614.888.0246 PHONE (OUTSIDE U.S.)
614.841.6022 FAX

VIA LEONARDO DA VINCI 8
ZONA INDUSTRIALE TOGNANA
35028 PIOVE DI SACCO (PD)
ITALY
39 049 9719 111 PHONE
39 049 5841 257 FAX

EMERSON NETWORK POWER ASIA PACIFIC
7/F., DAH SING FINANCIAL CENTRE
108 GLOUCESTER RD, WANCHAI
HONG KONG
852 2 572 2201 PHONE
852 2 802 9250 FAX

LIEBERT WEB SITE

<http://www.liebert.com>

24 x 7 TECH SUPPORT

800 222 5877 PHONE
614 841 6755 (OUTSIDE U.S.)

Due to continuing product improvement, specifications are subject to change without notice. Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

© 2004 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice. All names referred to are trademarks or registered trademarks of their respective owners.

® Liebert and the Liebert logo are registered trademarks of the Liebert Corporation.

® Keeping Business in Business is a registered trademark of the Liebert Corporation.

The Emerson logo is a trademark and service mark of Emerson Electric Co.

SL-30504 (R3/04)
Printed in USA

