



PowerSure PST

Sensible Power Protection In A Compact Package



- Three Battery-Backed UPS Outlets with space for transformer blocks
- Two Surge-Only Outlets
- Lightning and Surge Protection (TVSS)
- Data Line Surge Suppression (1 Input / 2 Output)
- USB Communication
- Full Sequenced Battery Testing
- Advance Early Warning Shutdown
- 2 Year Warranty

The Liebert PowerSure PST is an Off-Line UPS designed for individual desktop protection. The orange outlets provide battery and surge protection for your computer and monitor, while the black outlets protect your printer and scanner from surges. Data-Line protection for Phone / Fax / Internet / DSL / Modem is also provided.

The PST gives you more than enough time to save your files and shutdown your system. An alarm will sound when only two minutes of runtime are left; and with the USB communications, you can shutdown automatically when running Windows 2000, XP or Mac OS X 10.2 (or later).

Ideally Suited for:

- Desktop PC's
- Workstations
- Other Sensitive Electronics



Specifications

Model Number	PA350-120U	PA500-120U
Power Rating VA/W	350 / 225	500 / 300
Dimensions: In (mm)		
Unit WxDxH	6.6 x 9.8 x 3.7 (167 x 249 x 94)	
Weight: lbs (kg)		
Unit	11.7 (5.3)	13.5 (6.1)
Input AC Parameters		
Surge Protection	570 J	
Voltage Range w/o Battery Operation	98 VAC - 140 VAC ±3VAC	
Input Power Cord	attached 6.5 ft (2 m), w/NEMA 5-15 P	
Output AC Parameters		
Output Receptacles	(3) NEMA 5-15R (orange) battery backup + surge protection (2) NEMA 5-15R (black) Surge protection	
Voltage (Battery mode)	120VAC ±8%	
Output Current	2.9 A	4.2 A
Waveform (battery mode)	Stepped Sinewave	
Frequency	60Hz ±1Hz	
Battery Backup Time: minutes		
Pentium II w 15" Monitor	19	25
Pentium II w 17" Monitor	12	18
Pentium II w 21" Monitor	11	15
Pentium III w 15" Monitor	10	14
Pentium III w 17" Monitor	9	13
Pentium III w 21" Monitor	6	9
Pentium 4 w 15" Monitor	8	11
Pentium 4 w 17" Monitor	6	9
Pentium 4 w 21" Monitor	-	6
Recharge Time	12 Hours to 90% capacity	



Status indicators let you know the condition of the UPS.



All outlets are spaced to accommodate transformer plugs.



USB port offers communication to shut down if an outage ever exceeds battery capacity.



Data-Line protection ensures that your communication outlets (Phone / Fax / DSL / Internet / Modem) are also protected.

Liebert Corporation

1050 Dearborn Drive
P.O. Box 29186
Columbus, Ohio 43229
800 877-9222 (US)
614 888-0246 (Outside US)
614 841-6022 Fax

Via Leonardo Da Vinci 8
Zona Industriale Tognana
35028 Piove Di Sacco
Italy
39 049 9719 111 Phone
39 049 5841 257 Fax

23/F Allied Kajima Bldg.
138 Gloucester Road
Wanchai
Hong Kong
852 2 572 2201 Phone
852 2 831 0114 Fax

Liebert Web Site
www.liebert.com

24x7 Tech Support
800 222 5877 Phone
614 841 6755 (Outside US)
upstech@liebert.com E-mail

While every precaution has been taken to ensure accuracy and completeness in this literature, Liebert Corporation assumes no responsibility, and disclaims all liability resulting from use of this information or for any errors or omissions.

©2002 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice.

All names referred to are trademarks or registered trademarks of their respective owners.

®Liebert and the Liebert logo are registered trademarks of the Liebert Corporation.

® Keeping Business in Business is a registered trademark of the Liebert Corporation.

The Emerson logo is a trademark and service mark of Emerson Electric Company.

SL-23277 (1/03)
Printed in USA

Liebert is a division of

