



**VALVE REGULATED
LEAD ACID BATTERY (V.R.L.A.)**



**ADVANCED ABSORBED GLASS
MAT TECHNOLOGY (A.G.M.)**



**LONG DURATION BATTERIES
DESIGNED FOR MAXIMUM LIFE**



10 VOLT CONFIGURATION AVAILABLE !

Features

- Flame-retardant polypropylene case and cover compliant with UL94 V-0 with an Oxygen Limiting Index of greater than 28%.
- Gas recombination greater than 99%.
- Operates at a low internal pressure.
- Never needs watering, minimal maintenance.
- 99.7% pure lead, calcium alloy grids.
- Shock absorbent thick wall polypropylene cases.
- Cold forged non-porous terminal bushings, eliminate post leakage.
- Thermally welded case to cover bond, eliminates both acid and electrical leaks.
- Over-sized, through the partition inter-cell welds provide low resistance connections, with minimal power loss.
- Flame arresting, low pressure safety release venting system for individual cells, recognized per U.L. 924.
- Measured high vacuum acid fill, reduces electrical variability between cells.
- 100% recyclable materials.

Options




- Terminal covers.
- Inter-connecting battery cables.
- Custom wire harnesses.

Specifications

Cells per unit	6
Nominal voltage	12
Terminal type	Lead type "L"
Short circuit current	1883 amps
Impedance @ 77°F 25°C	7.33 milliohms
Weight lbs / kgs	26.7 / 12.1
Electrolyte (S.G.)	1.300
Capacity @ 77°F (25°C)	29 AH (8 hrs) to 1.75 V.P.C.
Ideal operating temperature range	+68°F (+20°C) to +77°F (+25°C)
Extended operating temperature range	Discharge: -40°F (-40°C) to +140°F (+60°C) Charge: -4°F (-20°C) to +122°F (+50°C)
Float Voltage	13.5 to 13.8 @ 77°F (25°C)
Recommended maximum charging current	C/4 amperes at 100% discharge Unlimited at partial discharge.
AC ripple from charging source	1.5% peak to peak of float
Storage period without recharge	6 months at 77°F (25°C)

No transport restrictions

- Surface transport. Classified as non-hazardous material as relates to DOT-CFR Title 49 part 171-189.
- Maritime transport. Non hazardous as per IMDG amendment 27.
- Air transport. Non hazardous complies with IATA / ICAO, special provision A67.



KS6 cabinet model

POWER BATTERY offers an extensive line of pre-wired and fused battery cabinets complete with UL and CUL approval. Standard and custom DC voltages complete with breakers and chargers are available.

Battery Cabinet Systems (pre-wired with TL-1230 batteries)							
Battery cabinet model	Maximum # of batteries	Dimensions					
		inches			millimeters		
		H	W	D	H	W	D
KS3	4	8.75	7.75	24.0	222	197	610
KS4	4	13.0	11.5	19.0	330	292	482
KS5	6	15.75	15.0	25.0	400	381	635
KS6	8	17.75	16.0	34.5	451	406	876
KS7	16	37.25	16.0	34.5	946	406	876
CR1	24	43.0	24.0	32.5	1092	610	826
CR3	36	43.0	40.0	32.5	1092	1016	826

Hours discharge rates in constant current (Amperes) and constant power (Watts) @ 77°F (25C°)														
Volts per cell		I	2	3	4	5	6	7	8	9	10	12	24	48
1.75	Amps	20.3	11.8	8.57	6.74	5.54	4.72	4.12	3.65	3.29	2.98	2.55	1.37	0.74
	* Watts	248	150	108	86.2	72.0	62.1	54.5	48.4	43.5	39.5	33.2	17.7	9.70
1.80	Amps	20.0	11.7	8.49	6.62	5.45	4.66	4.07	3.62	3.26	2.97	2.52	1.36	0.72
	* Watts	245	144	105	83.8	69.9	59.9	52.3	46.4	41.6	37.8	32.0	17.1	9.30
1.85	Amps	19.2	11.4	8.20	6.40	5.28	4.51	3.94	3.50	3.15	2.87	2.44	1.31	0.67
	* Watts	237	139	101	80.2	66.8	57.3	50.1	44.5	40.0	36.3	30.8	16.4	8.70
1.90	Amps	17.7	10.6	7.69	6.03	4.98	4.24	3.69	3.26	2.93	2.65	2.23	1.21	0.64
	* Watts	223	129	93.1	74.0	62.3	53.6	47.4	42.5	38.2	34.7	29.5	15.7	8.40

* For 10 Volt models reduce the Watts by 18%

U.S.A.
Power Battery Company, Inc.
25 McLean Blvd.
Paterson, N.J. 07514-1507
Phone: (973) 523-8630
Fax: (973) 523-3023
E-mail: sales@powbat.com
Web page: www.powerbattery.com

CANADA
Power Battery (Iberville) Ltd.
770 Thomas Ave.
Iberville, Québec, J2X 5E7
Phone: (450) 346-3273
Fax: (450) 346-8003
E-mail: powerbat@sympatico.ca
Web page: www.powerbattery.com

UK
Power Batteries Ltd.
Premier Way, Abbey Park Industrial Estate
Romsey, Hampshire, SO51 9AQ
Phone: +44 (0)1794 835900
Fax: +44 (0)1794 835910
E-mail: sales@powbat.co.uk
Web page: www.powbat.co.uk

ITALY
Power Battery Srl
Via Locatelli 105
20046 Biassono MI - ITALY
Phone: +(39) 039 2324571
Fax: +(39) 349 2499200
E-mail: calberti@powbat.it
Web page: www.powbat.it