

XTREME POWER CONVERSION M90L

Modular Online UPS // 208/120VAC Three-Phase

For more information, visit www.xpcc.com/m90l



Mission Critical Availability while reducing costs with Scalable, Modular M90 for 20kVA, 40kVA, 60kVA applications

The M90 is a scalable modular online double conversion UPS that protects critical data and equipment from power problems while supplying clean and reliable network grade power.

M90 can be configured with a fully redundant power modules. Should one module fail, the remaining modules smoothly take over the load. Because the power modules are independent, they can be hot swapped without risk to the critical load.

As power requirements change, M90 modularity makes it easy to add modules and increase capacity.

PRODUCT SNAPSHOT

- › Three capacities: 20kVA/18kW, 40kVA/36kW, 60kVA/54kW
- › Modular for capacity or redundancy
- › Hot swappable power modules
- › Up to 98% ECO mode or 94% online efficiency
- › Remote control and monitoring options
- › 2 years UPS warranty (USA and Canada)

FEATURES

Scalable—when power requirements change M90 modularity makes it easy to add modules and increase capacity

Highest availability—system can be configured with redundant power modules

Reduce energy cost—best-in-class energy efficiency provides lowest energy consumption and heat output

Dual or single utility input—provides maximum installation flexibility

Extended battery packs—external battery cabinets available for extended runtime

Maintenance bypass—manually transfer critical loads from UPS power to utility power, enabling M90 maintenance

Large LCD display—5.7" display provides graphic display including status and alarms

XTREME
Power Conversion®

Protect your business.

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/m90l

MODEL NUMBER		M90L-20	M90L-40	M90L-60
CAPACITY	Power Rating	20kVA/18kW	40kVA/36kW	60kVA/54kW
	Enclosure capacity: power modules	Up to 60kVA (3 x 20kVA)		
INPUT	Voltage/frequency nominal	208/120V, 50/60Hz auto-sensing		
	Voltage/frequency range	121VAC to 253VAC*		
OUTPUT	Voltage	208/120V		
	Frequency	50/60Hz ± 0.5Hz		
	THD (full load)	< 2%		
	Efficiency	Up to 98% ECO mode, 94% online mode		
	Overload capacity	105%-110% for 60min; 110%-125% for 10min; 126%-150% for 1min; >150% for 200ms		
DIMENSIONS & WEIGHT	Enclosure	20.3"W x 39.4"D x 30"H / 227 lbs		
	Power module	19.0"W x 28.0"D x 5.1"H / 74 lbs		
ENVIRONMENT	Temperature	0-40°C (32-104°F)**		
	Altitude	5,200 ft above sea level**		
	Audible Noise	< 65dBA at 1m		
APPROVALS		UL-1778 (TUV), cUL, FCC A, RoHS		
WARRANTY (UPS)		2 years (USA and Canada)		
COMMUNICATIONS INTERFACE		RS-232, EPO, intelligent slot for optional cards (Web/SNMP, Relay, Modbus)		
INCLUDED IN BOX		User manual, RS-232 cable, Ramp for unloading UPS enclosure		
AVAILABLE OPTIONS		External maintenance bypass, 480V input transformer, output distribution, external battery pack battery, battery temperature sensor		

*Depending on load level **Battery life is reduced above 30°C, UPS capacity derates above 30°C and 5,200 ft above sea level

BATTERY PACK DATA & RUNTIMES

Battery Cabinet Model	Battery Model	Strings	20kVA/18kW	40kVA/36kW	60kVA/54kW	Dimensions (W x D x H)	Weight
2TC1S280-D2401BXXX	HRL12280WFR	1	35	12	6.2	29.5 x 31.6 x 59.0 in	1,600 lbs
2TC1S330-D2401BXXX	HRL12330WFR	1	42	16	8.0	29.5 x 31.6 x 59.0 in	1,770 lbs
2TC1S390-D2401BXXX	HRL12390WFR	1	50	19	10	29.5 x 31.6 x 59.0 in	1,920 lbs
2TC1S540-D2401BXXX	HRL12540WFR	1	78	31	17	29.5 x 31.6 x 59.0 in	2,480 lbs
2TC1S620-D2401BXXX	XHRL12620WFR	1	82	36	20	29.5 x 31.6 x 59.0 in	2,480 lbs
55C2S330-D2401BXXX	HRL12330WFR	2	89	42	24	40.0 x 29.5 x 76.7 in	3,300 lbs
55C2S390-D2401BXXX	HRL12390WFR	2	106	50	29	40.0 x 29.5 x 76.7 in	3,600 lbs
55C2S540-D2401BXXX	HRL12540WFR	2	175	78	47	40.0 x 29.5 x 76.7 in	4,720 lbs
55C2S620-D2401BXXX	XHRL12620WFR	2	177	82	52	40.0 x 29.5 x 76.7 in	4,720 lbs

For extended runtimes and detailed requirements, call (800) 582-4524. Runtimes are shown in minutes and will vary based on battery age and site conditions.

Maintenance Bypass
full wrap around maintenance bypass with static switch interface

Cable Entry
cable entry for M90L is on rear, side or bottom



M90L back view



M90L Extended Battery Pack

X-TREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2017 Xtreme Power Conversion Corporation. All Rights Reserved. M90L01U (3/10/17)