

Powerware 9170+ 15kVA

To Receive Detailed Quotation Call: 800-306-1125

Condition	Pre-owned				
Model	9170+ 12 Slot				
Phase	Single Phase				
KVA	15				
Input Voltage	208-240				
Output Voltage	120/208 or 120/240				
Frequency (Hz)	60				
Dimensions H x W x D	Inches 60.7" x 24" x 28"				
Weight	427 lbs				
Warranty	90 Days				
Price	\$ 7,550.00				



Data Sheet: http://www.unitedpb.com/documents/powerware/9170+.pdf

Hardware Description:

Includes:

- (1) 12 Slot 9170+ Enclosure Beige
- (5) ASY-0673 9170+ 3kVA Power Modules(10) ASY-0529 9170+ Battery Modules (3) Strings NEW Batteries
- (1) SNMP/Web Card add <u>\$ 360.00</u>
- (1) External Make Before Break Bypass add <u>\$ 600.00</u>

Powerware 9170+ Runtime Charts

Runtime Chart in minutes (full load / half load) Split-Phase Module ASY-0673 Load (VA) Number of Strings (2 battery modules per string)												
	1 String	2 String	3 String	4 String	5 String	6 String	7 String	8 String	9 String	10 String	11 String	12 String
3 kVA	6.5/16	16/40	27.5/67.5	40/98	53.5/132	67.5/167	83/204	98/242	15/283	132/324	149/365	167/408
6 kVA		6.5/16	11/27.5	16/40	21.5/53.5	27.5/68	33.5/83	40/98	46.5/15	53.5/132	60.5/149	575/167
9 kVA			65/16	9.5/23.5	13/31.5	16/40	20/49	23.5/58	27.5/67.5	31.5/78	35.5/88	40/98
12 kVA				6.5/16	9/21.5	11/27.5	13.5/33.5	216/40	19/46.5	21.5/53.5	24.5/60.5	27.5/68
15 kVA					6.5/16	8/20.5	10/25	12/30	14/35	16/40	18.5/45	20.5/50.5
18 kVA						6.5/16	8/20	9.5/23.5	11/27.5	18/44	14.5/35.5	16/40

Powerware 9170+ Features



Powerware 9170+ 6-slot configuration

LCD Panel





3 kVA Power or Charger Module (1 per slot)

Communication Cards





Battery Module (2 per slot)

Maximum Performance

- The lowest overall cost of ownership is a direct result of the low initial investment, higher operating efficiencies and programmable high efficiency
- A UPS solution that is as easy to install and operate as a PC. Universal components fit in any order in any slot without affecting the operation of the system or its protection of the critical load
- Featuring user-friendly LCD display and two internal communication slots, which accept a wide variety of connectivity devices and the new SNMP/Web adapter card
- Lightweight, high-performance power and battery modules weigh under 30 lbs. for easy service and hot swapping

Maximum Reliability

- N+X power and logic redundancy eliminates single point-of-failure providing highest reliability and availability
- Redundant modularity virtually eliminates downtime and enhances serviceability
- ▶ ABM doubles battery service life

Maximum Availability


- Double conversion online technology is universally recognized as providing the highest availability in an internetcentric global marketplace
- Provides protection against power surges, spikes, sags, line noise, and lightning

Maximum Service Plans

- ▶ Powerware Gold Plan Plus Enhance and extend your standard UPS warranty with added assurance of knowing your UPS is installed and operated properly from the start
- ▶ Comprehensive coverage for the entire UPS
- On-site start-up by authorized Powerware Representative
- Replacement UPS or module delivered to your locations
- Original UPS or module picked up from your locations
- ▶ Please call for details

Maximum Flexibility

- Modular design delivers scalable flexible solutions to constantly changing equipment requirements
- Easily expanded by installing additional power, charger, or battery modules to support additional critical applications and devices
- Internal Options: galvanic isolation, line cord, receptacles, communications
- External options: Rack-mount kit, casters (standard on 9- and 12-slot enclosures), extended runtime battery cabinets (housing up to 8 hours of additional runtime), wall-mounted maintenance bypass cabinets



Adding yet another level of flexibility to the unique design of the Powerware 9170+ is the ability to transform a solution configured in a free-standing enclosure into a rack-mount solution by simply adding a rack-mount kit. Imagine all the standard benefits of the Powerware 9170+ in 3- and 6-slot configurations installed in a standard 19 inch computer rack.

