

# XTREME POWER CONVERSION V80

Value Series Pure Sine Wave Line Interactive UPS // 120V

For more information, visit [www.xpcc.com/V80](http://www.xpcc.com/V80)



## Value series line interactive power protection for servers and network equipment

V80 is a pure sine wave line interactive UPS that protects critical data and equipment from power problems while supplying clean and reliable network grade power.

V80 units have the highest efficiency ratings available, providing utility cost savings at all load levels. V80 design provides flexible mounting including tower, rack, or optional wall mounting. V80 models combine high performance with value pricing.

For line interactive models with additional features, reference the P80 at [www.xpcc.com/P80](http://www.xpcc.com/P80)

### PRODUCT SNAPSHOT

- › Available models: 700VA, 1000VA, 1500VA, 2000VA
- › Pure sine wave output
- › Automatic voltage regulation (AVR)
- › Tower, wall, 2-post and 4-post rack mounting configurations available
- › UL and cUL listed, RoHS compliant
- › 3 years electronics, 3 years battery warranty (USA and Canada)

### FEATURES

**Ease of use**—plug-and-play functionality means the UPS is ready to start backing up your equipment right out of the box

**Auto restart**—after full battery discharge, the V80 automatically restarts when utility power returns

**96% efficient operation**—high efficiency ECO mode lowers energy consumption

**Sleek design**—modern and compact, perfect for use in any home office or small office setting

**Smart LCD display**—vital monitoring and precise information from the front panel

**Maintenance bypass**—an optional XBDM bypass module enables the V80 to be serviced or replaced without interruption of power to critical loads

**\$50,000 load protection policy**—protection against damaged connected equipment

# MODEL SELECTION GUIDE

For more information, visit [www.xpcc.com/v80](http://www.xpcc.com/v80)

MODEL NUMBER		V80-700	V80-1000	V80-1500	V80-2000
CAPACITY	Power rating	700VA (420W)	1000VA (600W)	1500VA (900W)	2000VA (1200W)
INPUT	Voltage nominal	120VAC			
	Voltage range	82-148VAC			
	Frequency	50/60Hz auto sensing			
OUTPUT	Voltage	120VAC			
	Waveform	Pure sine wave			
	Transfer time (typical)	2-6ms			
	Efficiency	Up to 96% ECO mode, 93% buck and boost mode			
	Harmonic distortion	2% @ 100% linear load; 5% @ 100% non-linear load			
BATTERY	Battery type	Sealed, maintenance-free lead acid			
	Battery quantity and size	(1) 12V 9AH	(2) 12V 7AH	(2) 12V 9AH	(2) 12V 9AH
	Charging current	1A max			
	Typical recharge	4 hours to 90%			
PHYSICAL	Dimensions (W x D x H)	17.2" x 16.1" x 3.5"			
	Weight	24 lbs	27.3 lbs	29.3 lbs	31.3 lbs
	Line cord (removable)	6ft, 5-15P to C13			6ft, 5-20P to C19
	Receptacles	(8) NEMA 5-15R			
ENVIRONMENT	Operating temperature	32-104°F (0-40°C)			
	Audible noise	< 40dBA		< 45dBA	
	Altitude	11,500 ft above sea level			
APPROVALS	UL, cUL, RoHS				
WARRANTY	3 years electronics, 3 years battery warranty (USA and Canada)				
COMMUNICATIONS INTERFACE	USB				
INCLUDED IN BOX	Line cord, tower pedestals, user manual, USB cable, Xtreme Power Monitor software				
AVAILABLE OPTIONS	5 year extended warranty, bypass distribution (XBDM), power distribution (XPDU), 4-post rail kit, 2-post shelf kit, wall mount bracket				

## BATTERY RUNTIMES

Internal batteries					
Percentage load:	25%	50%	75%	100%	
V80-700	31	13	7	4	
V80-1000	33	15	10	5.5	
V80-1500	31	13	7	4	
V80-2000	15	6	4	2	

Runtimes are shown in minutes and will vary based on battery condition, age, cycles, and ambient temperature.



**X-TREME**  
Power Conversion®

Protect your business.

XPC USA / Denver, CO / [sales@xpcc.com](mailto:sales@xpcc.com)

XPC EMEA / Rotterdam, NL / [emea@xpcc.com](mailto:emea@xpcc.com)

[www.xpcc.com](http://www.xpcc.com)

©2017 Xtreme Power Conversion Corporation. All Rights Reserved. V80.01U (Rev 03/15/17)